SILFAB COMMERCIAL NTC

SIL-520 QM

SILFAB SOLAR®

NEXT-GENERATION N-TYPE CELL TECHNOLOGY

Manufactured exclusively in the USA.

- Increased Performance in High Temperatures
- Enhanced Durability
- Lower Temperature Coefficient
- Reduced Degradation Rate
- 25-Year Product Warranty/ 30-Year Performance Warranty

SILFABSOLAR.COM

ELECTRICAL SPECIFICATIONS		520	
Test Conditions		STC	NOTC
Module Power (Pmax)	Wp	520	384
Maximum power voltage (Vpmax)	V	40.48	37.24
Maximum power current (Ipmax)	A	12.85	10.31
Open circuit voltage (Voc)	V	47.52	43.71
Short circuit current (Isc)	A	13.65	10.96
Module efficiency	%	21.9%	
Maximum system voltage (VDC)	V	1500	
Series fuse rating	A	25	
Power Tolerance	Wp	0 to +10	

Measurement conditions: STC 1000 W/m² • AM 1.5 • Temperature 25 °C • NOCT 800 W/m² • AM 1.5 • Measurement uncertainty ≤ 3%
Sun simulator calibration reference modules from Fraunhofer Institute. Electrical characteristics may vary by ±5% and power by 0 to +10W.

MECHANICAL PROPERTIES / COMPONENTS	METRIC	IMPERIAL
Module weight	26.2kg ± 0.2kg	57.8lbs ± 0.4lbs
Dimensions (H x L x D)	2098 mm x 1133 mm x 35 mm	82.6 in x 44.6 in x 1.37 in
Maximum surface load (wind/snow)*	2400 Pa rear load / 5400 Pa front load	50.1 lb/ft² rear load / 112.8 lb/ft² front load
Hail impact resistance	ø 25 mm at 83 km/h	ø 1 in at 51.6 mph
Cells	132 Half cells - N-Type Silicon solar cell 182 mm x 91 mm	132 Half cells - N-Type Silicon solar cell 3.58 x 7.16 in
Glass	3.2 mm high transmittance, tempered, DSM antireflective coating	0.126 in high transmittance, tempered, DSM antireflective coating
Cables and connectors (refer to installation manual)	1350 mm, ø 5.7 mm, EVO2 from Staubli	53.15 in, ø 0.22 in (12AWG), EVO2 from Staubli
Backsheet	High durability, superior hydrolysis and UV resistance, multi-layer dielectric film, fluorine-free PV white backsheet	
Frame	Anodized Aluminum (Silver)	
Junction Box	UL 3730 Certified, IEC 62790 Certified, IP68 rated, three diodes	

TEMPERATURE RATINGS	
Temperature Coefficient Isc	+0.04 %/°C
Temperature Coefficient Voc	-0.24 %/°C
Temperature Coefficient Pmax	-0.29 %/°C
NOCT (± 2°C)	45 °C
Operating temperature	-40/+85 °C

WARRANTIES	
Module product workmanship warranty	25 years**
Linear power performance guarantee	30 years
	≥ 98% end 1st yr ≥ 94.7% end 12th yr ≥ 90.8% end 25th yr ≥ 89.3% end 30th yr

CERTIFICATIONS	
Product	UL 61215, UL 61730, CSA C22.2#61730, IEC 61215, IEC 61730, IEC 61701 (Salt Mist Corrosion), IEC 62716 (Ammonia Corrosion), CEC Listing, UL Fire Rating: Type 1
Factory	ISO9001:2015

SHIPPING SPECS	
Modules Per Pallet:	29 or 29 (California)
Pallets Per Truck	24 or 23 (California)
Modules Per Truck	696 or 667 (California)

* ⚠ Warning. Read the Safety and Installation Manual for mounting specifications and before handling, installing and operating modules.
** 12 year extendable to 25 years subject to registration and conditions outlined under "Warranty" at silfabsolar.com
PAN files generated from 3rd party performance data are available for download at: silfabsolar.com/downloads



SILFAB SOLAR INC.

1770 Port Drive
Burlington WA 98233 USA
T +1 360.569.4733
info@silfabsolar.com
SILFABSOLAR.COM

7149 Logistics Lane
Fort Mill SC 29715 USA
T +1 839.400.4338

4080 Confederation Parkway, Suite 301
Mississauga ON L5B 0G4 Canada
T +1 905.255.2501

Sales & Customer Support
T +1.833.998.6642

Silfab - SIL-520-QM-20260101
No reproduction of any kind is allowed without permission. Data and information is subject to modifications without notice. © Silfab Solar Inc., 2022. Silfab Solar® is a registered trademark of Silfab Solar Inc.